

**Product Data Sheet**  
Edition 14/10/2014  
Identification no:  
02 07 04 10 350 0 000003  
SikaProof® Patch-200 B

## SikaProof® Patch-200 B

Self-adhesive tape for external jointing of the SikaProof® A waterproofing system

<b>Product Description</b>	SikaProof® Patch-200 B is a self-adhesive tape, consisting of a SikaProof® membrane laminated with a Sikaproof® Butyle® adhesive that is covered with a release liner.
<b>Uses</b>	SikaProof® Patch-200 B is used for post-sealing of joints, penetrations as well as damages outside on the membrane side of the SikaProof® A-05/-08/-12 system.
<b>Characteristics / Advantages</b>	<ul style="list-style-type: none"> <li>■ High watertightness tested according various standards</li> <li>■ Weathering resistant with temporary UV-stability</li> <li>■ High adhesion of the SikaMelt® adhesive</li> <li>■ Easy and fast to install</li> </ul>

### Product Data

<b>Form</b>							
<b>Appearance / Colors</b>	White release liner over adhesive on a light yellow membrane.						
<b>Packaging</b>	2 rolls, packed in one cardboard box						
<b>Dimension</b>	<table border="1" style="width: 100%;"> <tr> <td>Width</td> <td>200 mm</td> </tr> <tr> <td>Length</td> <td>20 m</td> </tr> <tr> <td>Thickness</td> <td>2.2 mm</td> </tr> </table>	Width	200 mm	Length	20 m	Thickness	2.2 mm
Width	200 mm						
Length	20 m						
Thickness	2.2 mm						

<b>Storage</b>	
<b>Storage Conditions / Shelf Life</b>	SikaProof® Patch-200 B rolls have a shelf life of 18 months from date of production if stored properly in unopened undamaged original packaging, in a horizontal position, in dry conditions and at temperatures between +5°C and +30°C. The rolls must be protected from direct sunlight, rain, snow and ice, etc. Do not stack pallets of the rolls on top of each other, or under pallets of any other materials during transport or storage.

### Technical Data

<b>Compatibility</b>	<p>SikaProof® Patch-200 B is approved to seal only the SikaProof® A-05/-08/-12 system. To use SikaProof® Patch-200 B with other material (such as any synthetics etc.) the compatibility has to be tested.</p> <p>Not suitable for use in direct contact with PVC; tar, asphalt, hot bitumen, wood preservatives with substances containing oil, solvents or any other de-bonding agents.</p>
----------------------	---



---

## System Information

---

**Accessory** SikaProof® Patch-200 B is an ancillary product for the SikaProof® A-05/-08/-12 sheet membrane waterproofing system.

---

## Application Details

---

**Substrate quality** The contact surface is the light yellow membrane side of the SikaProof® A-05/-08/-12 membrane. It must be dry, clean and free of any materials that could impair the adhesion.

---

### Application Conditions /

#### Limits

**Substrate temperature** +5° C min. / +35 °C max.

---

**Ambient air temperature** +5° C min. / +35 °C max.

---

## Application Instructions

---

**Application Method** SikaProof® Patch-200 B is a cold-applied and post-applied self-adhesive tape to seal joints, connections, penetrations and possible damages of the membrane on the outside membrane side of the SikaProof® A-05/-08/-12 system. There is only a pressure roller required, to press the tapes firmly onto the membrane surface.

For further more detailed information about the installation method, please refer to the SikaProof® A-05/-08/-12 membrane Product Data Sheet and the Method Statement.

---

**Notes on Application / Limitations** SikaProof® A-05/-08/-12 system must only be installed by trained and approved Sika contractors.

SikaProof® A Patch-200 B is not UV stabilised and can not be installed on structures permanently exposed to UV light and weathering.

Do not apply the SikaProof® Patch-200 B during continuous or prolonged rainfall.

---

## Value Base

---

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

---

## Local Restrictions

---

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

---

## Ecology, Health and Safety Information

---

A Material Safety Data Sheet following EC- Regulation 1907/2006, Article 31 is not required to bring this product to the market, to transport, or to use it. The product does not damage the environment when used as specified.

---

## REACH

European Community Regulation on chemicals and their safe use (REACH: EC 1907/2006)

This product is an article within the meaning of Regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. Therefore, there are no registration requirements for substances in articles within the meaning of Article 7.1 of the Regulation.

Based on our current knowledge, this product does not contain SVHC (substances of very high concern) from the list published by the European Chemicals Agency in concentrations above 0.1 % (w/w).

## Legal Notes

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



### SIKA LIMITED

Head Office · Watchmead · Welwyn Garden City · Hertfordshire · AL7 1BQ · United Kingdom  
Phone: +44 1 707 394444 · Fax: +44 1 707 329129 · [www.sika.co.uk](http://www.sika.co.uk)

