

**Product Data Sheet**  
Edition 29/01/2016  
Identification no:  
02 07 04 41 010 0 000002  
Sika® BituSeal Primer

# Sika® BituSeal Primer

## BituSeal Primer

---

|                            |  |
|----------------------------|--|
| <b>Product Description</b> | Sika® BituSeal Primer is a bitumen solution to be used in conjunction with Sika® BituSeal S-115. |
|----------------------------|--|

---

|             |  |
|-------------|--|
| <b>Uses</b> | Sika® BituSeal Primer is used as a primer for Sika® BituSeal S-115 to increase adhesion and bond to the substrate. |
|-------------|--|

---

|                                     |  |
|-------------------------------------|--|
| <b>Characteristics / Advantages</b> | <ul style="list-style-type: none"><li>■ High adhesion and bonding ability on various substrates</li><li>■ Good binding ability for dust and loose particles</li><li>■ Ready to use by brush, roller or spray</li></ul> |
|-------------------------------------|--|

---

### Product Data

---

#### Form

|                             |              |
|-----------------------------|--------------|
| <b>Appearance / Colours</b> | Black liquid |
|-----------------------------|--------------|

---

|                  |              |
|------------------|--------------|
| <b>Packaging</b> | 25 ltr drums |
|------------------|--------------|

---

#### Storage

|                                       |  |
|---------------------------------------|--|
| <b>Storage Conditions/ Shelf life</b> | 18 months from date of production. Store in dry conditions between +5°C to +35°C. Rolls must be stored in their original package, in vertical position and under cool and dry conditions. They must be protected from direct sunlight, rain, snow and ice. |
|---------------------------------------|--|

---

### Technical Data

---

|                      |                  |
|----------------------|------------------|
| <b>Chemical Base</b> | Bitumen Solution |
|----------------------|------------------|

---

|                  |        |
|------------------|--------|
| <b>Viscosity</b> | 500 cP |
|------------------|--------|

---

|                       |     |
|-----------------------|-----|
| <b>Solids Content</b> | 48% |
|-----------------------|-----|

---

|                    |        |
|--------------------|--------|
| <b>Flash Point</b> | > 39°C |
|--------------------|--------|

---

|                 |                        |
|-----------------|------------------------|
| <b>Coverage</b> | 6-8m <sup>2</sup> /ltr |
|-----------------|------------------------|

---

|            |                |
|------------|----------------|
| <b>WFT</b> | 90-110 microns |
|------------|----------------|

---

|            |               |
|------------|---------------|
| <b>DFT</b> | 45-60 microns |
|------------|---------------|

---

Construction



## Application Instructions

### Application Method / Tools

Consumption rate approx. 350g/m<sup>2</sup> depending on substrate type and temperature.  
 Application by brush or roller.  
 Waiting time, depending to temperature, > 30min. unless drying.  
 For more detailed information, please refer to the current Method Statement of the according system.

### Notes on Application / Limits

This product must not be installed on wet substrates.  
 Apply at temperatures above +10°C. At lower temperatures, use a hot air gun or indirect flame to aid adhesion.  
 Never attempt to apply at temperatures below +5°C.

### Value Base

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

### Local Restrictions

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

### Health and Safety Information

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet containing physical, ecological, toxicological and other safety-related data.

### Legal Notes

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



#### SIKA LIMITED

Head Office · Watchmead · Welwyn Garden City · Hertfordshire · AL7 1BQ · United Kingdom  
 Phone: +44 1 707 394444 · Fax: +44 1 707 329129 · [www.sika.co.uk](http://www.sika.co.uk)