

Product Data Sheet
Edition 20/05/2016
Identification no:
02 07 04 31 002 0 000003
Sika BentoShield® Paste

Sika BentoShield® Paste

Thixotropic polymer modified natural sodium bentonite mastic

Product Description Sika BentoShield® Paste is a single component mastic consisting of polymer modified natural sodium bentonite and further polymer additives. Trowel applied and thixotropic in nature.

Uses Sika BentoShield® Paste used to:

- Seal Sika BentoShield® MAX LM membrane around vertical & horizontal penetrations
- Seal Sika BentoShield® MAX LM membrane around vertical & horizontal protrusions, eg metal anchors, metal conductors
- Seal ground level termination details
- Create secondary fillets at wall / slab junctions
- Correct minor cracks in the substrate prior to the membrane application
- Seal the vertical laps of membrane applications

Characteristics / Advantages

- Immediate activation, does not require to be mixed with water.
- Can be applied by trowel, putty knife or hand.
- Continuous waterproofing paste for irregular detailing
- Contains no bitumen or tar.
- Can be applied over metal & concrete surfaces

Product Data

Form

Appearance / Colour Brown paste

Packaging 15 Litre Pails

Storage

Storage Conditions / Shelf Life 24 months from date of production if stored properly in undamaged unopened, original sealed packaging, in dry conditions at temperatures between +5°C and +25°C. Protect from direct sunlight and frost.

Technical Data

Chemical Base 100% natural mineral, Montmorillonite, sodium bentonite, oil

Density Approx 1.90 Kg/Litre

pH Value 9.5 ±0.5

Construction



System Information

Application Details Sika BentoShield® Paste is a single component product which requires no further activation.
Can be directly applied to either dry or wet substrate.
It is recommended to remove loose concrete when applying Sika BentoShield® Paste on segregated concrete surfaces.

Consumption / Dosage Applied as a 40mm x 40mm triangular fillet : approx 15 linear metres

Application Conditions / Limitations Sika BentoShield® Paste can be directly applied to either dry or wet substrate.
Do not apply into pooling water.

Compatibility Sika BentoShield® Paste may be combined with other Sika products.
Important: Always conduct trials before combining products in specific mixes and contact the Sika Technical Service Department for information and advice about any specific combinations.

Application Instructions

Cleaning of Tools Clean all tools and application equipment with water immediately after use.
Hardened / cured material can only be removed mechanically.

Notes on Application / Limitations All dirt, contaminates and debris must be removed from the area of application.
Product must not be applied into standing water.

Excessive water addition or overdosing may cause bleeding or segregation.

Frost:

If frozen and / or if precipitation has occurred, Sika BentoShield® Paste may be used after thawing slowly at room temperature followed by intensive remixing.

Value Base All technical data stated in this Product Data Sheet are based on laboratory tests.
Actual measured data may vary due to circumstances beyond our control.

Local Restrictions Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

Health and Safety Information For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet containing physical, ecological, toxicological and other safety-related data.

Legal Notes The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



SIKA LIMITED

Head Office · Watchmead · Welwyn Garden City · Hertfordshire · AL7 1BQ · United Kingdom

Phone: +44 1 707 394444 · Fax: +44 1 707 329129 · www.sika.co.uk

