

Product Data Sheet
Edition 18/05/2016
Identification no:
02 07 04 31 002 0 000011
Sika BentoShield® Termination Strip

Sika BentoShield® Termination Strip

Galvanised steel fixing strip of membrane termination

Product Description Sika BentoShield® Termination Strip is a galvanised steel bonding strip with 5mm holes at 15mm centres in a solid plastic holder.

Uses Sika BentoShield® Termination Strip is used for fixing and sealing the top edge of Sika BentoShield® MAX LM on vertical sections.

- Characteristics / Advantages**
- Corrosion resistant
 - Secure fixing
 - Easy and fast to install

Product Data

Form

Appearance / Colors Galvanised steel roll in a red plastic holder

Packaging 10 rolls, packed in one cardboard box

Dimension

Width	12 mm
Length	10 m
Thickness	1.0 mm

Storage

Storage Conditions / Shelf Life Store in a dry place, safe from weathering and mechanical damage. Store at temperatures between +5°C and +35°C.

Technical Data

Material Hot dipped, galvanised steel.

System Information

Accessory Sika BentoShield® Termination Strip is an ancillary product for the Sika BentoShield® MAX LM membrane waterproofing system.

Application Instructions

Application Method Sika BentoShield® Termination Strip is used to seal the top edge of Sika BentoShield® MAX LM against ingress of water. It is fixed in place with the Sika BentoShield® Fixing System.

For further more detailed information about the installation method, please refer to the Sika BentoShield® MAX LM membrane Product Data Sheet and the Method Statement.



Notes on Application / Limitations	The Sika BentoShield® MAX LM system must only be installed by trained contractors.
Value Base	All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.
Local Restrictions	Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.
Ecology, Health and Safety Information	A Material Safety Data Sheet following EC- Regulation 1907/2006, Article 31 is not required to bring this product to the market, to transport, or to use it. The product does not damage the environment when used as specified.
Legal Notes	The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



SIKA LIMITED

Head Office · Watchmead · Welwyn Garden City ·

Hertfordshire · AL7 1BQ · United Kingdom

Phone: +44 1 707 394444 · Fax: +44 1 707 329129 · www.sika.co.uk

