



BS EN 13967:2012

14

0836

## DECLARATION OF PERFORMANCE

### Sika® BituSeal S-115

02	07	04	99	900	0	000073	1172
----	----	----	----	-----	---	--------	------

<b>1. Product Type:</b> Unique identification code of the product-type:	Sika® BituSeal S
<b>2. Type</b> batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):	-115 (Batch No See packaging)
<b>3. Intended use</b> or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:	<b>Prefabricated self-adhesive bituminous waterproofing sheet with HDPE film total 1.5mm thick according to EN 13967 (type T)</b>  <b>Damp proofing and waterproofing of all kinds of below ground structures</b>
<b>4. Name, registered trade name</b> or registered trade mark and contact address of the manufacturer as required under Article 11(5):	<b>Sika® BituSeal S-115</b>  <b>Sika Limited</b> <b>Watchmead</b> <b>Welwyn Garden City</b> <b>Hertfordshire</b> <b>AL7 1BQ</b> <b>United Kingdom</b>
<b>5. Contact Address:</b> Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):	Not Relevant (see 4)
<b>6. AVCP:</b> System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V:	System 2+
<b>7. Notified body (hEN):</b> In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard:	<b>0836</b> <b>Notified factory production control certification body No. 0836 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control (FPC) 083613/FO32</b>

Declaration of Performance



<b>8. Notified body (ETA):</b> In case of the declaration of performance concerning a construction product for which a European Technical Assessment (ETA) has been issued:	<b>Not relevant (see 7)</b>
--	-----------------------------

**9. Declared performance**

Essential Characteristics	Performance	Test Standard	Harmonised technical specification
Water tightness to liquid water	Pass	EN 1928 Method A 60 Kpa	EN 13967:2012 Product Type T
Resistance to Static Load	kg ≥ 20	EN 12730	
Durability of Watertightness against ageing	Pass	EN 1847 Method A 60 KPa	
Durability of Watertightness against chemicals	Pass	EN 1847 Method A 60 KPa	
Resistance to Impact	mm ≥ 500	EN 12691	
Resistance to tear (Nail Shank) CD	N ≥ 100	EN 12310-1	
Resistance to tear (Nail Shank) MD	N ≥ 100	EN 12310-1	
Reaction to Fire	Euro Class Class F	EN 13501	
Shear resistance of joints	N/50mm Long ≥ 180 Cross ≥ 200	EN 12317-1	
Flexibility at low temperature	°C -23	EN 1109	
Durability after artificial ageing / Watertightness	Pass	EN 1296/EN 1928	



**10. Declaration**

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

**Signed for and on behalf of the manufacturer by:**



R&D Manager



Technical Manager

05, 2015

---

**Ecology, Health and Safety Information (REACH)**

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet (MSDS) containing physical, ecological, toxicological and other safety related data.

---

---

**Legal note:**

This information is given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

---



SIKA LIMITED

Head Office · Watchmead · Welwyn Garden City · Hertfordshire · AL7 1BQ · United Kingdom

Phone: +44 1 707 394444 · Fax: +44 1 707 329129 · [www.sika.co.uk](http://www.sika.co.uk)

